



Commercial Sectional Steel Doors

H-300U Series



Energy efficiency and Durability

Hörmann commercial steel doors are available in a wide range of styles, sizes and design options. Sophisticated engineering and state-of-the-art manufacturing provide the basis for durable, reliable and long-lasting quality products.

H-300U doors offer 1-3/4" thick two sided steel ribbed sections and CFC free polyurethane insulation with an R value of 16.4 for exceptional energy efficiency and structural integrity.



H-300U three layer construction with polyurethane insulation

Energy Efficiency



Thermal Break

The top and bottom of each section has a 1/8" gap between the two steel joints which provides a thermal break.


Insulation

Polyurethane insulation is a two component bulk system. It is laid in during the manufacturing process and is self-laminating to each skin during a continuous curing cycle.

Twin Joint Seal

Sections are equipped with bi-directional twin seals.

Durability



Steel Reinforcement Plate

Provides structural integrity and rigidity to each section. Insures solid attachment of hardware to each section.

Embossed Exterior Surface

The exterior skin is made of 26 ga. galvanized steel in ribbed design. The exterior surface is painted with a two-coat paint system.

Design your door from our range of options

Panel designs



Ribbed design

Colors



White (standard) **Brown** (optional)

All colors shown as accurately as printing technology allows.

Windows



Window 24" x 12"*



Full View

*Windows come with insulated glass as standard. The number of windows available per section depends on the door width, please see chart below.

Surface finish




Stucco

Optional features

Flexible Top Seal

A flexible top seal is installed on the top section of the door and seals the door to the header.



Perimeter Jamb Seal

A bi-directional jamb seal is installed on the ends of each section.



Section/window arrangements and additional options



Ask for these and other Hörmann brochures at your local dealer.

Section Arrangement

Door Height	No. of Sections
Up to 8'0"	4
8'9" to 10'0"	5
10'3" to 12'0"	6
12'3" to 14'0"	7
14'3" to 16'0"	8
16'3" to 18'0"	9
18'3" to 20'0"	10

Window Arrangement

Door Width	Maximum No. Of Windows
Up to 8'2"	2
8'3" to 12'2"	3
12'3" to 16'2"	4
16'3" to 18'2"	5
18'3" to 20'2"	6
20'3" to 23'2"	7
23'3" to 24'2"	8

Options

- Keyed or inside slide lock
- Various track options
- Extended cycle springs 25k, 50k, 100k
- Chain hoist operation
- Full range of electric openers and safety devices

Everything you've wanted in a commercial door, and more.



Call us ► 1 877 OK HORMANN (1-877-654-6762)

Hörmann LLC, 5050 Baseline Road, Montgomery, Illinois 60538
 Phone: 630-859-3000 Fax: 630-859-8122 Email: info@hormann.us www.hormann.us

